

# Nexus Series® Commercial Louvres

Louvreclad Nexus Series® 100mm deep aluminium louvres feature a weather lip for enhanced rain protection. Ideal for plant rooms, air intakes, and louvre doors, and designed with a horizontal linear aesthetic.

## Features

### PERFORMANCE

#### Optimal Rain Defence

AS 4740:2025 verified Class B rain resistance up to 1.5 m/s core velocity, with CFD-verified Class A performance for the two-stage configuration. AS 4740:2025 verified Class 2 to Class 4 aerodynamic performance.

### AESTHETICS

#### Robust and Customisable

Ideal for plant rooms, air intakes, and exhausts. Nexus Series® includes standard, drainable, and two-stage louvres for tailored performance in various commercial and industrial applications.

### DESIGN

#### High-Performance Ventilation

Designed for areas with high weather exposure, ensuring maximum airflow and rain defence. Suitable for large industrial louvre banks and cyclonic conditions.

## Specifications

### AUSTRALIAN STANDARDS

AS 4740:2025/2000 CFD

### FINISH

Powder coated or anodised

### ORIENTATION

Horizontal

### ACCESSORIES

Bird/vermin mesh Insect mesh  
Rain sensors Dampers Dust filters  
Security screens and bars  
Integrated louvred doors

### MATERIAL

6060 T5 Extruded Aluminium

### INSTALLATION

Installation and mounting details will be designed in accordance with proprietary systems and recommendations as designed and manufactured by Louvreclad.

# Explore the profile options

## Nexus Series®

Versatile extruded aluminium louvres with weather lip



**Class 2**

AERODYNAMICS

**0.53 CD**

DISCHARGE COEFFICIENT

**0.183 m<sup>2</sup>**

EFFECTIVE AERODYNAMIC AREA

**50 %**

FREE OPEN AREA

**102 mm**

DEPTH

**125**

PITCH

**1200 mm**

MAX SPAN

**11kg/m<sup>2</sup>**


WEIGHT

**Horizontal**

ORIENTATION

## Nexus Series® Drainable

Drainable extruded aluminium louvres



**Class 2**

AERODYNAMICS

**0.54 CD**

DISCHARGE COEFFICIENT

**0.185 m<sup>2</sup>**

EFFECTIVE AERODYNAMIC AREA

**50 %**

FREE OPEN AREA

**102 mm**

DEPTH

**125**

PITCH

**1350 mm**

MAX SPAN

**12kg/m<sup>2</sup>**



WEIGHT

**Horizontal**

ORIENTATION

## Nexus Series® Two Stage

Two-stage extruded aluminium louvres



**Class 4**

AERODYNAMICS

**0.28 CD**

DISCHARGE COEFFICIENT

**0.096 m<sup>2</sup>**

EFFECTIVE AERODYNAMIC AREA

**50 %**

FREE OPEN AREA

**204 mm**

DEPTH

**125**

PITCH

**1350 mm**

MAX SPAN

**30kg/m<sup>2</sup>**

WEIGHT

**Horizontal**

ORIENTATION

# AS 4740:2025 Rain Resistance

## Nexus Series®

Rain penetration classification at each core velocity.

Ventilator core velocity (m/2)	0	0.5	1	1.5	2	2.5	3	3.5
Effectiveness E (%)	99%	99%	98%	97%	90%	69%	45%	31%
Classification	Class A	Class B	Class B	Class B	Class C	Class D	Class D	Class D

The results concluded the ventilator has fair rain resistance performance at the core velocities from 0-3.5m/s as summarised in the table above. The average rain penetration effectiveness for this model was 80% in Class C rating.

## Nexus Series® Drainable

Rain penetration classification at each core velocity.

Ventilator core velocity (m/2)	0	0.5	1	1.5	2	2.5	3	3.5
Effectiveness E (%)	86%	84%	84%	83%	80%	78%	75%	72%
Classification	Class C	Class C	Class C	Class C	Class C	Class D	Class D	Class D

The results concluded the ventilator has fair rain resistance performance at the core velocities from 0-3.5m/s as summarised in the table above. The average rain penetration effectiveness for this model was 80% in Class C rating. (AS 4740:2000 CFD Verified only)

## Nexus Series® Two Stage

Rain penetration classification at each core velocity.

Ventilator core velocity (m/2)	0	0.5	1	1.5	2	2.5	3	3.5
Effectiveness E (%)	100%	100%	100%	100%	100%	100%	99.50%	95.70%
Classification	Class A	Class A	Class A	Class A	Class A	Class A	Class A	Class B

The results concluded that the ventilator has excellent rain resistance performance at the core velocity from 0-3m/s as summarised in the table above. The average rain penetration effectiveness for this model was 99% under Class A rating. (AS 4740:2000 CFD Verified only)

## Technical Data Disclaimer

- Indicative maximum span provided are based on generic permissible design wind pressure of 2kPa.
- Span values and product technical information provided are subjected to variance by project specific requirements & influence factors such building location, terrain category & local pressure effects.
- Span values provided are based on typical scenario where product specified are fixed at one end; simply supported at the other end and in either horizontal or vertical orientation.
- If the product specified is required to function as barrier for fall protection or as trafficable element, maximum span and pitch nominated may be reduced.
- Spans values provided could be influenced and reduced when used in dynamically sensitive wind environment.
- Nexus Series® Drainable and Nexus Series® Two Stage Rain Resistance: Compliance verified by AS 4740:2000 CFD analysis only.

For project specific product selection or preliminary design & engineering consultation, please contact 1300 165 678 or [sales@louvreclad.com](mailto:sales@louvreclad.com) to arrange or book a meeting.




## Inspire with Quality

As leaders in the building envelope market, we are known for exceptional quality and lasting value. Our credibility, wealth of knowledge, and unmatched competence enable us to inspire exterior solutions that look good and perform better.



## The MadeRight Guarantee

Following our proven process enables us to develop solutions we're proud to put our mark of quality to. We guarantee that all projects will be delivered in a timely manner, be on specification, engineered to Australian standards and finished to the highest quality.



## Made to Perform

Louvreclad solutions are made to last and manufactured on-site using high-quality Australian aluminium and steel. As an organisation we are driven to get a thousand things right everyday to achieve our vision to be the face of Australian Building. Our facades are not here to be average, they are here to perform – and so are we.

# Speak to an expert

Reach out today to discuss your facade solution requirements; we would love to hear from you.



Made to Perform

1300 165 678

[sales@louvreclad.com](mailto:sales@louvreclad.com)

[louvreclad.com](http://louvreclad.com)