

Louvreclad Sheraton Series® 75mm modular aluminium sun blades offer ellipsoid, bullet, and panel configurations. Supporting vertical spans up to 4.5m, they're ideal for shading in cyclonic regions.

Features

PERFORMANCE

Superior Strength

75mm modular sun blades support vertical spans up to 4.5m, ideal for cyclonic regions. Engineered for durability and long-lasting performance.

AESTHETICS

Architectural Versatility

Available in ellipsoid, bullet, and panel configurations. Provides a distinctive look for building facades, enhancing visual appeal.

DESIGN

Flexible Installation

Suitable for vertical and horizontal mounting. Concealed mounting options available for a sleek finish. Delivered readymade for single-trade installation.

Specifications

ORIENTATION

Horizontal or Vertical

OPERATION OPTIONS

Fixed, Electric motor, Manual winder

MATERIAL

6060 T5 Extruded Aluminium

INSTALLATION


Installation and mounting details will be designed in accordance with proprietary systems and recommendations as designed and manufactured by Louvreclad.

FINISH

Powder coated or anodised

Explore the profile options


Sheraton Panel




Sheraton Bullet



Sheraton Ellipsoid



Sheraton Chamfer




Sheraton Double Chamfer



Explore the typical configurations


Sheraton 440 Panel

440x75mm Panel




Sheraton 640 Panel

640x75mm Panel




Sheraton 520 Bullet

520x75mm Bullet




Sheraton 720 Bullet

720x75mm Bullet




Sheraton 600 Ellipsoid

600x75mm Ellipsoid




Sheraton 800 Ellipsoid

800x75mm Ellipsoid




Sheraton 360 Chamfer

360x75mm Chamfer




Sheraton 560 Chamfer

560x75mm Chamfer



Sheraton 480 Double Chamfer


480x75mm Double Chamfer



Typical Installation

Wall Mounting Channel

(Max width 1050mm without additional bracket)




Technical Data Disclaimer

- Indicative maximum span provided are based on generic permissible design wind pressure of 2kPa.
- Span values and product technical information provided are subjected to variance by project specific requirements & influence factors such building location, terrain category & local pressure effects.
- Span values provided are based on typical scenario where product specified are fixed at one end; simply supported at the other end and in either horizontal or vertical orientation.
- If the product specified is required to function as barrier for fall protection or as trafficable element, maximum span and pitch nominated may be reduced.
- Spans values provided could be influenced and reduced when used in dynamically sensitive wind environment.


For project specific product selection or preliminary design & engineering consultation, please contact 1300 165 678 or sales@louvreclad.com to arrange or book a meeting.






Inspire with Quality

As leaders in the building envelope market, we are known for exceptional quality and lasting value. Our credibility, wealth of knowledge, and unmatched competence enable us to inspire exterior solutions that look good and perform better.



The MadeRight Guarantee

Following our proven process enables us to develop solutions we're proud to put our mark of quality to. We guarantee that all projects will be delivered in a timely manner, be on specification, engineered to Australian standards and finished to the highest quality.



Made to Perform

Louvreclad solutions are made to last and manufactured on-site using high-quality Australian aluminium and steel. As an organisation we are driven to get a thousand things right everyday to achieve our vision to be the face of Australian Building.

Our facades are not here to be average, they are here to perform – and so are we.

Speak to an expert

Reach out today to discuss your facade solution requirements; we would love to hear from you.

